



# DECLARATION OF PERFORMANCE

DOP PVO 0502

1. Unique identification code of the product-type:

Loose-laid panels according to EN 16511 4,5 mm

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

LVT Pergo Optimum Click - Premium Click

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Unilin, division Flooring, Ooigemstraat 3 - B-8710 Wielsbeke, Belgium

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

not applicable

RUG - Vakgroep textielkunde / EPH - Dresden





Notified Body

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

## 9. Declared performance

| Essential characteristics         | Performance   | Harmonised technical specification |
|-----------------------------------|---|------------------------------------|
| Reaction to fire                  |  | EN 14041: 2004/AC:2006             |
| Content of Pentachlorophenol      |  | EN 14041: 2004/AC:2006             |
| Formaldehyd Emissions             |  | EN 14041: 2004/AC:2006             |
| Slip resistance                   |  | EN 14041: 2004/AC:2006             |
| Electrical behavior (dissipative) | NPD   | EN 14041: 2004/AC:2006             |
| Electrical behavior (conductive)  | NPD   | EN 14041: 2004/AC:2006             |
| Electrical behavior (antistatic)  | NPD   | EN 14041: 2004/AC:2006             |
| Thermal conductivity [W/mK]       | Th res (m2K/W) = 0,02   | EN 14041: 2004/AC:2006             |
| Water-tightness                   | not applicable  | EN 14041: 2004/AC:2006             |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Jasper de Jaeger, technical services manager

(name and function)

Wielsbeke, 14/11/2017

(place and date of issue)

(signature)